

V-BELTS

Quad-Power II		Raw edge, moulded notch, narrow section V-belt		Multi-ribbed belt		Micro-V®			
	XPZ	WIDTH mm	HEIGHT mm				PJ	HEIGHT mm	SPACING mm
	XPA	10	8				PL	3.60	2.34
	XPB	13	10				PM	6.40	4.70
	XPC	16	13					12.50	9.40
		22	18						

Super HC® MN		Raw edge, moulded notch, narrow section V-belt		Polyurethane multiple V-belt		Polyflex® JB™				
	SPZ	WIDTH mm	HEIGHT mm				5M	WIDTH mm	HEIGHT mm	SPACING mm
	SPA	10	8				7M	5	3.30	5.30
	SPB	13	10				11M	7	5.30	8.50
	SPC	16	13					11	7.10	13.20
		22	18							

Hi-Power® MN		Raw edge, moulded notch, conventional section V-belt		V-belt for variable speed drives		Multi-Speed							
	Z	WIDTH mm	HEIGHT mm				W16	WIDTH mm	HEIGHT mm		13	WIDTH mm	HEIGHT mm
	A	10	6				W20	16.6	5.0		23	13.0	6.0
	B	13	8				W25	20.7	6.5		28	23.0	8.0
	C	17	10				W31.5	25.9	8.0		37	28.0	9.0
		22	12				W40	32.6	10.0		47	37.0	10.0
							W50	41.5	13.0		47	47.0	13.0
							W63	51.8	16.0				
							W63	65.3	20.0				

PowerBand®		Multiple V-belt		V-belt for heavy-duty and clutching applications		PowerRated®			
	3VX	WIDTH mm	HEIGHT mm				2L	WIDTH inch	HEIGHT inch
	5VX	10	8				3L	1/4	1/8
	SPB	16	13				4L	3/8	7/32
	SPC	16	13				5L	1/2	5/16
		22	18			21/32	3/8		